

**TRANSAMERICAN STRUKTUROC™, INC.  
MATERIAL WARRANTY**

This Warranty is made for the benefit of the Purchaser only. This Warranty is non-transferable and non-assignable. No terms or conditions other than those stated herein, in any way purporting to modify this Warranty shall be binding on Strukturoc™.

**PANEL PERFORMANCE**

TransAmerican Strukturoc™ Inc. ("Strukturoc™") Signature Textued Wall Panels are Warranted for a period of Twenty (20) years from date of installation;

- a. Will not chalk in excess of ASTM D-659-80 number (8) rating.
- b. Will not change color more than five (8.0) Hunter E units as per ASTM D-2244-79.
- c. Will not crack or peel (adhesion). Not including minute fracturing occurring during Installation.

Strukturoc's liability under this Warranty will be limited to repainting or replacing any panel found to be not in compliance with this Warranty at Strukturoc's sole option. Strukturoc's liability shall be limited to furnishing (but not dismantling or installing) the necessary replacement materials request. Strukturoc™ shall not have any liability or responsibility for any consequential liquidated damages, including, without limitation, lost profits, down time, loss of plant or materials or any other incidental or consequential losses or expenses of any nature, whether such claims, damages or expenses shall be based on actions or claims arising in tort, including negligence, strict liability, contract, or breach of warranty, or any other claim or action of any description.

**FINISH**

In the event that the customer should decide to change/touch-up the finish of the Strukturoc™ wall panel system, the customer must purchase the paint from TransAmerican Strukturoc™ Inc. and use an approved and qualified painter in order for this warranty to be honored. Any deviation from this will immediately void the finish warranty and *TransAmerican Strukturoc™, Inc.* will not be held liable for any problems caused by not using the required paint and/or approved painter.

**CONDITIONS**

All claims made under this Warranty must be made within (15) days after discovery of defect, or from the date on which Installer reasonably should have known of such defect.

**EXCEPTIONS**

This Warranty expressly excludes any defect caused by improper handling by purchaser or installer, Acts of God, falling objects, external forces or loads, explosions, fire, riots, civil commotion, acts of war, vandalism, radicalism, inadequate foundations, discoloration due to mineral substances found in soil, whether in the atmosphere or otherwise, corrosion, or floods. A certain amount of waviness, commonly referred to as oil-canning is inherent in any flat panel manufactured from coiled steel. It is therefore not considered a defect and is not cause for rejection.

This Warranty requires compliance with Strukturoc's installation procedures. Any failure by purchaser including but not limited to, improper storage, transportation, erection, or placement shall in no manner be the liability of Strukturoc™. Ferrous shavings could rust or stain finish. Failure to remove it shall be in no manner the liability of Strukturoc™. This Warranty will not be effective and binding to TransAmerican Strukturoc™, Inc. until: (1) Payment in full for products has been received by TransAmerican Strukturoc™, Inc. (2) The Warranty has been signed by an officer of TransAmerican Strukturoc™, Inc. (3) a copy of this Warranty has been accepted and signed by the owner and returned to TransAmerican Strukturoc™, Inc.

**CLEANING INSTRUCTIONS**

In the event that dirt, mud or other contamination occurs on the panels surface, follow the steps outlined below.

- 1) A standard garden hose with pressure nozzle is usually sufficient to remove most jobsite contamination.
- 2) If a pressure sprayer is readily available, CAUTION should be exercised with its use. Pressure sprayers capable of over 3000 psi should not be held closer than 3 feet away from the panels surface and for sustained periods of more than 30 seconds in any particular area.
- 3) Stains that occur as a result of soil with high iron content can be particularly difficult to remove. It is not uncommon to have "splash-up" onto the lower wall as a result of eave conditions and uncompleted landscaping. If contamination is allowed to remain on the panel surfaces for a prolonged period (several days) a stain may occur. It is recommended that the removal of dirt be a part of daily clean-up which will help ensure that permanent staining does not occur.

If the methods above do not result in removal of the contamination, contact your customer service representative.

[Redacted]

Project Title:

[Redacted]

Address:

[Redacted]

Owner Signature

[Redacted]

TransAmerican Strukturoc, Inc.

[Redacted]

Owner (Please Print):

[Redacted]

City, State, Zip Code:

[Redacted]

Date:

[Redacted]

Date: